

Induction Burners & Beverage Pantry Equipment

RFI Line Items

ECPU:ESTIMATED COST P/UNIT

PMP:POTENTIAL MINIMUM PURCHASE

PAP:POTENTIAL ANNUAL PURCHASE

PF:PURCHASE FREQUENCY

ETD:ESTIMATED DELIVERY TIME

Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
Induction Burners - CookTek				16			1	10	CookTek Model No. 660801 (B651-U2) Incogneeto™ Induction Buffet, under-countertop design, mounts to underside of countertop, includes control panel & (1) Magneeto™ trive(locator/controller disc), auto
Beverage Pantry Equipment - BACK BAR CABINET, REFRIGERATED				1			1	10	BACK BAR CABINET, REFRIGERATED Perlick Corporation Model No. BBR72 Refrigerated Back Bar Cabinet, three-section, 72"W, remote refrigeration, 23.9 cu.ft. interior volume, (3) hinged doors with locks, LED interior lighting, automatic defrost, field-plumbed condensate; 120v/60/1-ph, 2.0 amps, hardwired; 1 yr. parts & labor warranty on all components except refrigeration; NOTE: This remote refrigerator includes choice of factory installed expansion valve. Solenoids, liquid & suction lines MUST BE provided by the refrigeration contractor even if the condensing unit is purchased from Perlick; No expansion valve; Standard refrigerator; Stainless steel top - no tapping holes; End finish: Stainless steel, unfinished, both sides, standard; Door type, first: solid, black vinyl clad; Door hinge location, first: Left; Door handle, first: full length stainless steel handle, 24"; Shelving style, first: (3) flat shelves; Door type, second: solid, black vinyl clad; Door hinge location, second: Left; Door handle, second: full length stainless steel handle, 24"; Shelving style, second: (3) flat shelves; Door type, third: solid, black vinyl clad; Door hinge location, third: Right; Door handle, third: full length stainless steel handle, 24"; Shelving style, third: (3) flat shelves; Crisp White™ LED
Beverage Pantry Equipment - PORTABLE BAR				1			1	10	PORTABLE BAR - FWE / Food Warming Equipment Co., Inc. Model No. SCB-8 Mobile Bar, 95"W, conventional beverage service, removable & adjustable shelf, (2) 60 lb. capacity ice bin with drains, sliding stainless steel cover, removable bottle speed rack, revolving underbar server with (4) bowls, towel ring, glass storage area with stainless steel shelf, stainless steel construction, no bumper, 5" casters (2) rigid, (4) swivel with brakes, NSF Two year limited parts & one year labor warranty, standard (6) 5" Casters standard: EZ Roll Heavy Duty Poly, (2) rigid, (4) swivel with brakes, standard
Beverage Pantry Equipment - DISHWASHER, UNDERCOUNTER				1			1	10	DISHWASHER, UNDERCOUNTER - Hobart Model No. LXGER-2 (6" LEG STAND)Advansys™ Undercounter Dishwasher/Glasswasher with Energy Recovery, Hot Water Sanitation, .62 gal per rack, 30 or 24 Racks/Hour, Fresh Water Rinse, Steam Elimination, Smart Sensing, Auto Delime notification & cycle, Auto Chemical Priming, with detergent, rinse aid & delime pumps, 2 Programmable Cycles, Advanced Service Diagnostics, electric tank heat, 120/208-240(3W)/60/1, ENERGY STAR®, Free factory startup for installations within a 100 mile radius of a Hobart service office; installation beyond 100 miles will be charged at the quoted rate by the local Hobart service office; Standard warranty - 1-Year parts, labor & travel time during normal working hours; NOTE: All LXGe Glasswashers ship with a leg stand assembled at the factory - additional leg stands are available as accessory parts
Beverage Pantry Equipment - REACH-IN REFRIGERATOR				1			1	10	REACH-IN REFRIGERATOR - Hoshizaki Model No. R3A-FS; Steelheart Series Refrigerator, reach-in, three-section, 79.03 cu. ft., self-contained refrigeration, solid state digital controller with temperature alarms & LED display, stainless steel interior & exterior (front & sides), standard depth, (3) field reversible solid doors, (9) adjustable shelves, (8) 4" heavy duty casters (3 with brakes), R290 Hydrocarbon refrigerant, (2) 1/4 HP, NEMA 5-15P, cETLus, ETLSanitation Warranty: 3-Year parts & labor on entire machine; Warranty: 5-Year parts on compressor 115v/60/1-ph, 9.5 amps, standard Casters, 4" (set of 8), standard NOTE: DOOR LOCKS ARE STANDARD ON THIS UNIT
				Totals					