

AAA-08-11-2017

RFI STATUS Submitted to county

PREPARED BY

DATE: 8/10/2017

Ballasts & Light Bulbs - RFI

RFI Line Items

Product Name	MFR	MTA product #	EQPU	Min Qty	PMP	PAP	PF	ETD	Details	ETD-ESTIMATED DELIVERY TIME
ECPU-ESTIMATED COST P/UNIT	PMP-POTENTIAL MINIMUM PURCHASE	MTA product #	EQPU	Min Qty	PMP	PAP	PF	ETD		
2 Lamp T8 Ballast	Sylvania	S5208		20			1	3	2 Lamp Universal Electronic Sylvania Ballast for 4' T8 Fluorescent Sylvania Light Bulb	
2 Lamp T8 Ballast	Sylvania	ICN2M32MC		20			6	3	2 Lamp - 120/277 volt - T8 - ICN-2M32-MC - Instant Start - Electronic - Centium Advance Fluorescent Ballast	
3 Lamp T8 Ballast	Sylvania	49945		20			6	3	(3) Lamp - F32T8 - 120/277 Volt - Instant Start - 0.88 Ballast Factor - QTP3X32T8/UNV/ISN	
4 lamp T8 Ballast	Sylvania	QTP4X32T8/UNV/ISN		20			4	3	OSRAM SYLVANIA QTP4X32T8/UNV-ISN-SC (49947) 4 FLUORESCENT Ballasts-Fluorescent-HID	
13 Watt CFL Ballast	Advance	ICF2S13H1LD35M		20			2	3	for use with (2) 13Watt CFL (4PIN) 120/277Volt compact fluorescent lamps	
(2) 26 Watt CFL Ballast	Advance	IZT-2S26-M5-BS		20			2	3	FOR 1OR 2 26 WATT CFL PIN LIGHTS	
54 WATT T5 Ballast	Universal	B254PUNV-D 2 Lamp T5		5			6	3	Brand Universal - Family AccuStart 5 - Voltage 120/277 - Ballast Factor 1 - Length 16.88 in. - Width 1.18 in. - Height 1 in. - Start Temp. Min 0 Deg. F - Power Factor 99 - Start Method Programmed Star	
26 Watt CFL Ballast	Universal	QTP 2x26/32/42CF/UNV		20			2	3	IntelliVolt? multiple-voltage technology enables operation at any input voltage from 120 to 277 volts, 50/60Hz	
42 Watt CFL Ballast	Universal	23829		20			2	3	C2642UNVME 000K 1 or 2 Lamp - 120 to 277 Volts - Operates 26/32/42 Watt Triple Tube Lamps, 26 Watt Quad Tube, 24 Watt Linear - Operates 28 and 32 Watt Butterfly Lamps (F282D/F382D)	
4 lamp T12 Ballast	Universal	B432I277RH		10			6	3	Universal Triad B432I277RH-A T8 Fluorescent Ballast	
(1-4) T12/HO4 32 ft Ballast	Philips Advance	ISB043214EI		10			2	3	Ballast, Fluorescent, Electronic, Instant Start, High Output	
Electronic Sign Ballast - 4-32 ft. Total	Hatch	ESB-0432-14-UV		10			2	3	electronic sign ballast features instant start circuitry, is RoHS compliant, and can be used with up to (4) T12/HO 800mA lamps	
T5 Fluorescent Ballast	Universal	B224PUNV-C		20			4	3	F24T5HO	

AAA-08-11-2017

RFI STATUS Submitted to county

PREPARED BY

DATE: 8/10/2017

Ballasts & Light Bulbs - RFI

Product Name	MFR	MFR product #	EQTL	Min Qty	PMP	PAC	PF	ETD	Details
(2) Lamp - F96T12/HO/ES	Universal	B295SRUNVHP000C		20			4	3	120/277 Volt - Instant Start - 0.88 Ballast Factor
T8 Fluorescent Ballast	Sylvania	49906		20			5	3	Instant Start Electronic Fluorescent Ballast for (1-2) F32T8 F40T8 F17T8 Lamps Operated at 120V/277V - OTP2X32T8/JUNV-1SN-SC-B
PLL40/41K 4-PIN Compact Fluorescent 2G11 Base	Philips	30044		50			3	2	40 Watt Compact Fluorescent 4100 Kelvin Color Temperature 4-Pin 2G11 Base 3150 Lumens 82 CRI, 20,000 Average Rated Hours 16.5" Maximum Overall Length.
PLL40/850K 4-PIN Compact Fluorescent 2G11 Base	Philips	30042		50			3	2	40 Watt Compact Fluorescent 3000 Kelvin Color Temperature 4-Pin 2G11 Base 3150 Lumens 82 CRI, 20,000 Average Rated Hours 16.5" Maximum Overall Length.
CF26DD/E/841/ECO	Sylvania	20669		100			4	2	26-Watt Double Tube Compact Fluorescent Light Bulb, 4100K, 1710 Lumens, 82 CRI, T4 Shape, 4-Pin G24q-3 Base, 12-pack
7MR16/F25 3000 DIM AF2 10/1	Philips	929001152904		48			3	2	
FO32/841/ECO	Sylvania	FO32/841/ECO		420			3	2	32 Watt 48" T8 Linear Fluorescent 4100K 85 CRI Medium Bipin (G13) Base Tube
F96T12/CW/HO-O/ALTO	Philips	38176-4		15			5	2	110 Watt - T12 - High Output - 4100K - Case of 15
F72T12/CW/HO/ALTO	Philips	36651-8		15			4	2	85 Watt - T12 - High Output - 4100K - Case of 15
F84T12/CW/HO	Sylvania	25384		15			5	2	Straight T12 Fluorescent Tube Light Bulb 4100K
F54T5/841/HO/ECO LAMP	GE	F54W/T5/841/ECO/SRC		40			3	2	54 Watt 46" T5 Linear Fluorescent 4100K 85 CRI Miniature Bipin (G5) Base Shatter Resistant Coated High Output Tube
8.5A19/27K/CL/ND	Philips	462309		48			3	2	60 Watt Equivalent Soft White A19 LED Clear Light Bulb, 8 Pack
13PAR30/LN/LED/40'/2700K/120V/D	SATCO	S9430		24			4	2	13 watt PAR30 Long Neck LED; 2700K; 40' beam spread; Medium base; 120 volts
13PAR30/SN/LED/40'/2700K/120V/FL	SATCO	S9415		24			4	2	LED PAR30 Bulb Short Neck - 13W - 75W Equivalent - 950 Lumens - 2700K
3.5W CTC/LED/27K/CL/120V	SATCO	S9922		10			4	2	3.5 watt CT1 LED; Clear; Candelabra base; 2700K; 350 lumens; 120 volts
6G25/LED/2700K/450L/120/DIMMABLE	SATCO	S9200		24			4	2	6 watt; G25 Globe LED; 2700K; Medium base; 120 volts

AAA-08-11-2017

RFI STATUS Submitted to county

PREPARED BY

DATE: 8/10/2017

Ballasts & Light Bulbs - RFI

Product Name	MFR	MFR Product #	ECU	Mfg Qty	PMP	PAU	PF	ETD	Details
7PAR20/LED/40/3000K/120V/DIMMABLE	SATCO	S9082		24			4	2	7 watt; LED PAR20 LED; 3000K; 40' beam spread; Medium base; 120 volts
4.5T10/LED/E26/27K/120V	SATCO	S9580		30			4	2	4.5 watt T10 LED; Clear; Medium base; 2700K; 430 lumens; 120 volts
ADVANCE CENTIUM ICN-2M32-MC	Philips	ICN-2M32-MC		40			2	2	Fluorescent Ballast; For Fluorescent, Electronic, Instant, 0° F Min Starting Temp, 59 W Input Watt
QUICKTRONIC Electronic Ballasts	Sylvania	CF26/32/42		20			4	2	CF26/32/42 120/277V BALLAST UNIVERSAL
FO32/830/ECO	Sylvania	21777		300			3	2	48" long, 3000K color temperature, 82 CRI, 32 watts, Energy efficient, operates on an electronic ballast.
Totals									