

AAA-10-02-2019

DATE:10/1/2019

HYSTER FORTIS CUSHION TIRE FORKLIFT

RFI Line Items

ECP:ESTIMATED COST P/UNIT PMP:POTENTIAL MINIMUM PURCHASE PAP:POTENTIAL ANNUAL PURCHASE PF:PURCHASE FREQUENCY ETD:ESTIMATED DELIVERY TIME

ECP:ESTIMATED COST P/UNIT	PMP:POTENTIAL MINIMUM PURCHASE	PAP:POTENTIAL ANNUAL PURCHASE	PF:PURCHASE FREQUENCY	ETD:ESTIMATED DELIVERY TIME
HYSTER FORTIS CUSHION TIRE FORKLIFT	HYSTER	1	1 10	SEE ATTACHED
Totals				



AAA-10-02-2019

Model: S50FT Available Features

HYSTER FORTIS CUSHION TIRE FORKLIFT MODEL S50FT. Nominal 5000 lb. capacity at 24" load center. Fortis trucks feature low operating costs, superior ergonomics, greater dependability, and exceptional productivity. Standard Equipment includes: Hyster Stability System, Integrated Dashboard Display, Operator Restraint System, Infinitely Adjustable Steering Column, Low Fuel Indicator, Duratread Floormat and Operator Presence System (OPS).

Proposal Summary

Included Items	Description	Quantity
Model	Hyster® FORTIS™ S50FT Lift Truck - 5,000 lb Nominal Capacity, Class IV	1
Powertrain	Brakes - Self Energizing Drum Engine - PSI 2.4L LPG Electronically Controlled Powershift 1-Speed Transmission	
Powertrain Options	High Air Intake Pressure Sensing Low LPG Fuel Indicator Single Pedal Inch/Brake Arrangement Swing Out LPG Tank Bracket 33.5 lb Steel LPG Fuel Tank with Auxiliary Fill Valve Anti-Clog Radiator Key Switch Start UL Label - Classification Type LP	
Powertrain Accessories	System Monitoring	
Mast	3 Stage Full Free Lift Mast - Class II - 189" (4800mm) Maximum Lift Height - 83" (2085mm) Overall Lowered Height - 60" (1546mm) Free Lift Height without Load Backrest - 238" (6023mm) Overall Extended Height with Load Backrest Mast Tilt - 5° Forward / 5° Back	
Carriages & Attachments	48" (1220mm) High Load Backrest Extension 38.5" (977mm) Wide - Class II - Hook Type Integral Sideshift Carriage	
Forks	42" Long x 1.6" Thick x 3.9" Wide (1067mm x 40mm x 100mm) - Class II Hook Type - Standard Taper Forks	
Hydraulics	3 Function (1 Auxiliary) Hydraulic Control Valve Mechanical Lever Hydraulic Controls - Cowl Mounted	
Hoses	1 Auxiliary Function Hose Group - 2 Hoses Internally Mounted	
Wheels & Tires	Drive Tires - 21 x 7 x 15 - Cushion - Non-Marking Compound - Smooth Tread - Standard Tread Width Steer Tires - 16 x 5 x 10.5 - Cushion - Non-Marking Compound - Smooth Tread	
Operator Compartment	Fire Extinguisher - 2.5 lb. Dry Chemical Rear Drive Handle with Horn Button 82" (2061mm) Overhead Guard - Grid Style	
Directional Control	MONOTROL® Directional Control Pedal Steering Wheel with Integral Spinner Knob	

Quote Number: 2019-257427



P100-50-01-AAA

Seat

Seat Belt - Black - No-Cinch with ELR (Emergency Locking Retractor)

Non-Suspension Vinyl Seat

Chassis Options

Fully Enclosed Hood and Side Panels - Non-Vented

Lights & Alarms

Audible Alarm - Reverse Direction Activated - Self-Adjusting 82-102 dB(A)

Visible Alarm - Amber LED Strobe - Keyswitch Activated - Does Not Increase Truck Height

Work Lights - Halogen Glass Lens - 2 Front and 1 Rear - Rear Combination Lights - LED - 2 Brake / Tail / Back-up

Warranty

12 Months / 2,000 Hours Manufacturer's Warranty, 36 Months / 6,000 Hours

Powertrain Warranty; please see full Warranty Statement for additional details.

Literature & Nameplate

English Literature Pack and Labels

