

AAA-10-31-2019-B

RFI STATUS: Submitted to county

DATE: 10/31/2019

Glass Curtain Control System

RFI Line Items											
ECU ESTIMATED COST PAIR1	PMP-POTENTIAL MINIMUM PURCHASE	PAP-POTENTIAL ANNUAL PURCHASE	PP-PURCHASE FREQUENCY	ETD-ESTIMATED DELIVERY TIME						Details	
grandMA3	grandMA3		1	1	25						Technical Specs: Parameters 8,192 (HTP/LTP) Parameters Mode2 4,096 (HTP/LTP) Operating voltage/ Supply voltage 100-240V, 50/60Hz Power max. 200VA Operating Temperature 0 °C up to 40 °C / 32 °F up to 104 °F Dimensions 482 x 372 x 87 mm / 19 x 15 x 4 in (width x depth x height) Net weight 5 kg / 12 lbs Connectors: 1 x powerCON TRUE1 2 x etherCON/R45
grandMA3	grandMA3		1	1	25						Technical Specs: Parameters 2,048 (HTP/LTP) Parameters Mode2 not applicable (no Mode2) Operating voltage/ Supply voltage 100-240V, 50/60Hz Power max. 50VA Operating Temperature 0 °C up to 40 °C / 32 °F up to 104 °F Dimensions 620 x 427 x 102 mm / 25 x 17 x 4 in (width x depth x height) Net weight 10 kg / 22 lbs Connectors 1 x IEC-60320 C14 cord 2 x DMX512-A Out (Spin XLR female) 1 x DMX512-A In (Spin XLR male) 1 x MIDI In (Spin DIN female) 1 x MIDI Out (Spin DIN female) 1 x Linear Timecode In (Spin XLR female)
Totals											