

AAA-11-30-2015-B

RFI ID: RFI054

RFI STATUS: SUBMITTED TO COUNTY

PREPARED BY: Jackie Ventura

DATE: 11/30/2015

BALLASTS

RFI Line Items

ITEM	MFR	MFR PART # / SKU	ECPU	MIN QTY	PMP	PAP	PF	ETD	DETAILS
2 Lamp T8 Ballast	Sylvania	S5208							2 Lamp Universal Electronic Sylvania Ballast for 4' T8 Fluorescent Sylvania Light Bulb
2 Lamp T8 Ballast	Sylvania	ICN2M32MC							2 Lamp - 120/277 volt - T8 - ICN-2M32-MC - Instant Start - Electronic - Centium Advance Fluorescent Ballast
2 Lamp T8 Ballast	Sylvania	49906							Primary Lamp: F32T8 - No. of Lamps: 2 - Input Voltage: 120/277 - Ballast Code: QTP2X32T8/UNV/ISN/SC
3 Lamp T8 Ballast	Sylvania	49945							(3) Lamp - F32T8 - 120/277 Volt - Instant Start - 0.88 Ballast Factor - QTPX32T8/UNV/ISN
4 lamp T8 Ballast	Sylvania	QTP4X32T8/UNV/ISN							OSRAM SYLVANIA QTP4x32T8/UNV-ISN-SC (49947) 4 FLUORESCENT Ballasts- Fluorescent-HID
70 watt metal Halide	Robertson	M70MLTLC3M-500K 70W							mHID, Ballast, Metal Halide, Pulse Start, 70 Watt (M98), HPF, 120/208/240/277Vac., 60Hz, Quad Tap, HX-HPF Ballast Kit
100 Watt Metal Halide	Robertson	3P10004							mHID, Ballast, Metal Halide, Pulse Start, 100 Watt (M90), HPF, 120/208/240/277Vac., 60Hz, Quad Tap, HX-HPF Ballast Kit
70 watt Metal Halide	ESPEN	MH170MV-LFS							Espan MH170MV/LFSVK Electronic HID Ballast/Ballasts limit the amount of current in an electric circuit. The current would rise to destructive levels in the lamp if it didn't have the ballast to limit it.
13 Watt CFL Ballast	Advance	ICF2S13H1LD35M							Advance ICF2S13H1LD35M CFL Electronic Ballast(This Philips Advance Electronic Ballast isnspp for use with (2) 13Watt CFL (4PIN) 120/277Volt compact fluorescent lamps.
(2) 26 Watt CFL Ballast	Advance	I2T-2S26-M5-BS							FOR 1OR 2 26 WATT CFL PIN LIGHTS.
42 Watt CFL Ballast	Advance	ICF-2S18-H1-LD							IntelliVolt? multiple-voltage technology enables operation at any input voltage from 120 to 277 volts, 50/60Hz
54 WATT T5 Ballast	Universal	B254PUNV-D 2 Lamp T5							Brand Universal - Family AccuStart 5 - Voltage 120/277 - Ballast Factor 1 - Length 16.88 in. - Width 1.18 in. - Height 1.1 in. - Start Temp. Min 0 Deg. F - Power Factor 99 - Start Method Programmed Start
26 Watt CFL Ballast	Universal	QTP 2x26/32/42CF/UNV							IntelliVolt? multiple-voltage technology enables operation at any input voltage from 120 to 277 volts, 50/60Hz
42 Watt CFL Ballast	Universal	23829							C2642UNVME 000K 1 or 2 Lamp - 120 to 277 Volts - Operates 26/32/42 Watt Triple Tube Lamps, 26 Watt Quad Tube, 24 Watt Linear - Operates 28 and 32 Watt Butterfly Lamps (F282D/F382D)

ECPU: ESTIMATED COST P/UNIT PMP: POTENTIAL MINIMUM PURCHASE PAP: POTENTIAL ANNUAL PURCHASE PF: PURCHASE FREQUENCY ETD: ESTIMATED DELIVERY TIME

4 lamp T12 Ballast

Universal

B432127RH

Universal Triad B432127RH-A T8 Fluorescent Ballast

Totals