

ONGOING CONSUMABLES - PLEATED AIR FILTERS

ITEM	MFR	MFR PART # / SKU	EST COST P/UNIT	MIN QTY	POTENTIAL MIN PURCHASE	POTENTIAL ANNUAL PURCHASE	PURCHASE FREQUENCY	ETD (MAXIMUM ALLOWED)	DETAILS
Extended Surface, Pleated Filter, MERV 8	AAF	12 x 20 x 2	\$2.80	48	\$134	\$134	ANNUAL	30 DAYS	Refer to next sheet for REQUIRED specifications
Extended Surface, Pleated Filter, MERV 8	AAF	12 x 24 x 2	\$2.80	12	\$34	\$34	ANNUAL	30 DAYS	Refer to next sheet for REQUIRED specifications
Extended Surface, Pleated Filter, MERV 8	AAF	16 x 20 x 2	\$2.75	12	\$33	\$33	ANNUAL	30 DAYS	Refer to next sheet for REQUIRED specifications
Extended Surface, Pleated Filter, MERV 8	AAF	20 x 20 x 2	\$3.15	420	\$1,323	\$1,323	ANNUAL	30 DAYS	Refer to next sheet for REQUIRED specifications
Extended Surface, Pleated Filter, MERV 8	AAF	20 x 24 x 2	\$3.60	480	\$1,728	\$1,728	ANNUAL	30 DAYS	Refer to next sheet for REQUIRED specifications
Extended Surface, Pleated Filter, MERV 8	AAF	20 x 25 x 2	\$3.55	80	\$284	\$284	ANNUAL	30 DAYS	Refer to next sheet for REQUIRED specifications
Extended Surface, Pleated Filter, MERV 8	AAF	24 x 24 x 2	\$3.95	180	\$711	\$711	ANNUAL	30 DAYS	Refer to next sheet for REQUIRED specifications
POTENTIAL ANNUAL SPEND:						\$4,247			

PLEATED AIR FILTERS

PRODUCT INFORMATION						PERFORMANCE DATA						
Nominal Sizes (Inches) (W x H x D)	Actual Sizes (Inches) (W x H x D)	Rated Airflow Pleats Capacity (SCFM) Per Filter			Pleats Per Filter	Pleats Per Lineal Foot	Rated Initial Resistance (in w.g.)			Recommended Final Resistance (in w.g.)	ASHRAE 52.2 MERV	Cont. Temp. Limit
		300 FPM	500 FPM	625 FPM			300 FPM	500 FPM	625 FPM			
12 x 20 x 2	11-1/2 x 19-1/2 x 1-3/4	500	850	1050	10	10	0.13	0.27	0.39	1	8	150°F / 66°C
12 x 24 x 2	11-3/8 x 23-3/8 x 1-3/4	600	1000	1250	10	10	0.13	0.27	0.39	1	8	150°F / 66°C
16 x 20 x 2	15-1/2 x 19-1/2 x 1-3/4	650	1100	1400	13	10	0.13	0.27	0.39	1	8	150°F / 66°C
20 x 20 x 2	19-1/2 x 19-1/2 x 1-3/4	850	1400	1750	17	10	0.13	0.27	0.39	1	8	150°F / 66°C
20 x 24 x 2	19-3/8 x 23-3/8 x 1-3/4	1000	1650	2100	17	10	0.13	0.27	0.39	1	8	150°F / 66°C
20 x 25 x 2	19-1/2 x 24-1/2 x 1-3/4	1050	1750	2150	17	50	0.13	0.27	0.39	1	8	150°F / 66°C
24 x 24 x 2	23-3/8 x 23-3/8 x 1-3/4	1200	2000	2500	20	10	0.13	0.27	0.39	1	8	150°F / 66°C