

BirdDog Camera

RFI Line Items

ECPU:ESTIMATED COST P/UNIT

PMP:POTENTIAL MINIMUM PURCHASE

PAP:POTENTIAL ANNUAL PURCHASE

PF:PURCHASE FREQUENCY

ETD:ESTIMATED DELIVERY TIME

Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
BirdDog Eyes P100 1080p Full NDI PTZ Camera (Black)	BirdDog	BDP100B		1			1	2	Entry-level Full NDI indoor PTZ camera Up to 1080p60 resolution 10x optical zoom ideal for small to mid-size environments Simultaneous 3G-SDI and NDI outputs Includes breakout cable with an Ethernet port (NDI), composite output, 3.5mm audio jacks, and RS-232/422/485 control ports 128 presets Up to 150°/s preset adjustment speed 350° continuous pan Auto, manual, and push focus 0.5 lux minimum illumination Includes BirdDog Comms Lite NDI audio intercom platform (Windows) Optional BirdDog Central software supported for decoding NDI back to SDI Optional BirdDog PTZ Keyboard supported. Image Sensor: 1-Chip 1/2.86" CMOS Sensor/ Sensor Resolution Effective: 2.2 Megapixel/ Minimum Illumination: 0.5 Lux/ Shutter Speed: 1/1 to 1/30,000 sec/ Max Digital Zoom12x/ Optical Zoom Ratio: 10x/ Focal Length: 4.7 to 47mm/ Field of View Horizontal: 6.43 to 60.9°/ Maximum Aperture: f/1.6 to 3/ Focus Control: Autofocus Manual Focus/ Output Formats: SDI, RJ45: 1920 x 1080p at 25, 29.97, 50, 59.94, 60 fps 1920 x 1080i at 50, 59.94, 60 fps 1280 x 720p at 25, 29.97, 50, 59.94, 60 fps/ Presets: 128/ Move Speed: 150°/sec/ Movement Range: Pan: 350°/ Tilt: -15 to 90°/ Tally Light: No Supported Control Protocols: Pelco-D VISCA/ Power Connectors: 1 x Barrel / Coaxial (12 VDC)/ Video Output Connectors: 1 x BNC (3G-SDI / HD-SDI / SD-SDI) Male 1 x RJ45 (NDI) 1 x RCA (Composite)/ Audio I/O: 1 x 1/8" / 3.5 mm Stereo Input: 1 x 1/8" / 3.5 mm Stereo Output/ Dimensions: 6.06 x 5.71 x 5.71" / 15.4 x 14.5 x 14.5 cm Weight: 2.2 lb / 1 kg
Totals									