

## Control Room purchases

RFI Line Items									
ECPU:ESTIMATED COST P/UNIT	PMP:POTENTIAL MINIMUM PURCHASE	PAP:POTENTIAL ANNUAL PURCHASE	PF:PURCHASE FREQUENCY	ETD:ESTIMATED DELIVERY TIME					
Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
Eclipse Tools PK-1900NA - Pro Electronics Tool Kit	Eclipse tools	PK-1900NA		1			1	2	The Eclipse Tools PK-1900NA is a pro electronics tool kit. The tool kit comes with a deluxe aluminum frame tool case. This kit is suitable for a wide variety of electronic applications. The kit also includes a rotary tool with many tips. Soldering iron and accessories are also included with this kit. A large assortment of hand tools is also a part of this kit. Utility Component Storage Box Dual Color Lineman's Plier Super Fine Tip Straight Tweezer 6in Adjustable Wrench 7-in-1 Tool for AWG18/16/14/12/10 Desoldering Pump IC Extractor Square Scraper/Stainless Steel Brush Slotted Shaft/Split 45 Lever Tapered Reamer/Tapered Needle Pen Solder 63% (3) Prong Holder Needle File Flat Needle File Round Needle File Square Needle File Triangle Needle File Semicircle PVC Insulated Tape Brush Black Handle 3/16in Socket Pro-Soft Screwdriver 1/4in Socket Pro-Soft Screwdriver T10H Security Star Tip (3.0 x 75mm) Pro-Soft Screwdriver T15H Security Star Tip (4.0 x 75mm) Pro-Soft Screwdriver 3 Slotted (3.0 x 75mm) Pro-Soft Screwdriver 5 Slotted (5 x 75mm) Pro Soft Screwdriver 6 Slotted (6 x 100mm) Pro-Soft Screwdriver No. 0 Phillips (3.0 x 75mm) Pro-Soft Screwdriver No. 1 Phillips (5 x 75mm) Pro-Soft Screwdriver No. 2 Phillips (6 x 100mm) Pro-Soft Screwdriver No. 2 Phillips (6 x 250mm) Pro-Soft Screwdriver Soldering Tip Cleaner Wrist Strap 10ft Utility Knife (3 Blades Self Loading) Folding Type Hex Key Set (Metric or inch) 10 Pcs Electronic Combination Wrench (Metric or inch) Flux Bottle (Unit: 2Pcs/Pack) Ø56mm Bulb Blower 3-1/2in Compact Digital Multimeter Voltage Detector Hobby Vise (Jaw Opening 40mm /Width 60mm Long Nose Plier (132mm) Diagonal Cutting Plier (109mm) Flat Nose Plier (135mm) Bent Nose Plier (128mm) 3.6V Li-ion USB Grinder Set No. 00 Phillips x 50mm Precision Screwdriver No. 0 Phillips x 75mm Precision Screwdriver No. 1 Phillips x 150mm Precision Screwdriver Flat (2.0 x 50mm Precision Screwdriver Flat (2.4 x 75mm) Precision Screwdriver Flat (3.0 x 100mm) Precision Screwdriver Ceramic Soldering Iron 110V Multi-Purpose Scissor Pallet for PK-1900N Series Top Pallet for PK-1900N Series Deluxe Aluminum Frame Tool Case
Moldex® SparkPlugs® Wall Mount Earplug Dispenser - Large	Moldex	S-18106		1			1	2	DIMENSIONS: Unit: 13 1/2 x 6 x 6" (L x W x H) MATERIAL: Acrylic polymer Natural latex free MOUNTING HARDWARE: Includes: 500 pairs (2) Wall anchors (2) Plastic drywall screws (1) Bracket USAGE: Non-refillable
ZEISS Lens Wipes	ZEISS	000000-2127-721		1			1	2	These Lens Wipes (60-Pack) from ZEISS provide an effective way to clean and preserve valuable optics. Whether used with camera lenses, eyeglasses, sunglasses, telescopes, or spotting scopes, these nona
ZEISS Microfiber Cleaning Cloth	ZEISS	2096-818		4			1	2	This Microfiber Cleaning Cloth from ZEISS can be used to wipe off various contaminants from camera lenses, eyeglasses, telescopes, spotting scopes, or other valuable optics. The fine microfiber materia
Beyerdynamic DT-290MKII 200/80 Ohms	Beyerdynamic	701610		2			1	2	Light Headset with Dynamic Microphone. ightweight, low profile design Reference quality, closed ear monitors High suppression of ambient noise Soft, circumaural ear pad Noise cancelling microphone Dynamic, hypercardioid microphone capsule Very high gain-before feedback Flexible gooseneck for optimal positioning Noise cancelling microphone Single exit, plug-in cable assembly
Beyerdynamic DT 280 MK II 200/80 Ohms Headset	Beyerdynamic	DT-280-MKII-200-80		2			1	2	The Beyerdynamic DT 280 MK II headset uses a dynamic headphone transducer with a frequency response of 10 - 30,000 Hz and excellent isolation from ambient noise. The single cable is detachable, the ear cushions are replaceable. The pivoting gooseneck microphone- boom design, can be swivelled to work on the left or right side of the headset, or set to the upper position when not in use. Good ambient noise attenuation High-quality dynamic hyper-cardioid microphone with very high gain-before-feedback NEW - Flexible, pivotable gooseneck for optimal positioning Lightweight, low profile design Single-sided, detachable cable NEW Limiter (Optional) Powerful neodymium headphone system for excellent reproduction accuracy Balanced sound impression Closed headphone Circumaural ear pads, advanced ear cushion system Adjustable, soft padded headband Service-friendly construction due to exchangeability of all parts
Used Sony 1-542-296 Electric Condenser Microphone G	SONY	VDXSO1542296		1			1	2	Capsule TypeMono Electret Condenser Frequency Response40 Hz to 20 kHz DirectivityUni directional (super-cardioid) Sensitivity *[1]-36 dB ±3 dB Output Impedance *[2]220Ω±20%, Balanced Dynamic RangePhantom: 107 dB or more Battery: 98 dB or more Signal-to-Noise Ratio *[3]77 dB or more Inherent Noise *[4]17 dB SPL or less Induction Noise From External Magnetic Field *[5]0 dB SPL or less Wind Noise *[6]50 dB SPL (without windscreen) 45 dB SPL or less (with windscreen) Maximum Input Sound Pressure Level *[7]Phantom: 124 dB SPL Battery: 115 dB SPL

### Control Room purchases

<p>CC-110-X5 Premium Lightweight Single On-Ear Intercom Headset</p>	<p>CLEARCOM</p>	<p>CC-110-X5</p>	<p>3</p>	<p></p>	<p>1</p>	<p>2</p>	<p>Clear-Com CC-110-X5 Premium Lightweight Single On-Ear Intercom Headset - 5-Pin Male XLR. Single-ear premium light-weight headset High quality dynamic cardioid microphone 20Hz -20KHz frequency response Choice of earpads: leatherette or foam Flexible gooseneck microphone positioning Boom rotation ON/OFF switch for quick microphone muting Interchangeable cabling for easy connector change and repair Fully serviceable headset Rugged design Specifications: Headphone Type: Closed-back Driver: 36mm diameter, neodymium magnet, copper-clad aluminum wire voice coil Frequency Response: 20Hz v- 20kHz Microphone Element: Dynamic Driver: 15mm, neodymium magnet Polar Pattern: Cardioid Frequency Response: 250Hz - 20kHz Sensitivity Open Circuit Sensitivity: -64 dB ±3.5 dB; at 1kHz, typical 99dB ±3 dB (SPL); at 1kHz typical Power Maximum: 500mW Impedance 400 ohms ±30%; at 1kHz typical</p>
<p>Samsung Business SR35 Series 22-Inch Computer Monitors</p>	<p>Samsung</p>	<p>LS22R350FHNXZA</p>	<p>2</p>	<p></p>	<p>1</p>	<p>2</p>	<p>1.8" 1920x1080 Ips Panel With 75Hz Refresh Rate Delivers Crisp, Stunning Images With A Wide Viewing Angle A Sleek Ultra-Slim Bezel Design Stands Out On Any Desk. Monitor Includes A Tilt-Adjust Stand</p>
<p>Dual 24"-35" Monitor Arm Desk Mount fits Two Flat/Curved Mon</p>	<p>AVLT</p>	<p>AVLT-DM15-1</p>	<p>1</p>	<p></p>	<p>1</p>	<p>2</p>	<p>FITS UP TO 15.6" LAPTOP &amp; 32" SCREEN Dual monitor desk mount fits most of flat/curved/ultrawide computer monitors up to 17.6 lb each in weight with VESA 75x75mm or 100x100mm mounting holes. Heavy-duty metal base only take up 5.7" x 4.3" desk surface. The c clamp and grommet mounting options support up to 1.9" desk thick. Mechanical spring monitor arm assists height adjustment from 7.6" to 17.7". Adjusting the monitor adapts to your posture by arm extension, vertical tilt, horizontal swivel, and landscape or portrait rotation. New top mounting design simplicity the assemble process. After locking a few screws, the monitor mounts instantly improve working posture, increase workspace, hide cables, and discover the most productive self. Friendly tech support to help with any questions or concerns. AVLT DM15-1 is covered by 3-YEAR MANUFACTURER WARRANTY and LIFETIME TECH SUPPORT.</p>
<p>BirdDog Eyes P200 1080p Full NDI PTZ Camera</p>	<p>BirdDog</p>	<p>BDP200B</p>	<p>1</p>	<p></p>	<p>1</p>	<p>2</p>	<p>Color Black - Image Sensor 1/2.8" CMOS Sensor Sensor Resolution Effective: 2.13 Megapixel Minimum Illumination 0.01 Lux at 1/30 Shutter Speed Camera Shutter Speed 1/1 to 1/10,000 sec Max Digital Zoom 12x Flip / Mirror Support Image Flip, Mirror (Vertical) Lens Optical Zoom Ratio 30x Focal Length 4.3 to 129mm Field of View Horizontal: 2.3 to 63.7° Maximum Aperture f1.6 to 4.7 Focus Control Autofocus Manual Focus Video Output Output Formats SDI, HDMI, RJ45: 1920 x 1080p at 25, 29.97, 50, 59.94, 60 fps 1920 x 1080i at 50, 59.94, 60 fps 1280 x 720p at 25, 29.97, 50, 59.94, 60 fps Control Presets 128 Move Speed 150°/sec Movement Range Pan: 350° Tilt: -30 to 90° Supported Control Protocols Pelco-D VISCA Interfaces Video Output Connectors 1 x RJ45 (NDI) 1 x BNC (3G-SDI) 1 x HDMI Type A (HDMI 1.4) Audio I/O 1 x 1/8" / 3.5 mm Stereo Input 1 x 1/8" / 3.5 mm Stereo Output Control Interface 1 x RJ45 (IP Control) Other I/O 2 x RJ45 (RS-232, RS-422, RS-485) 1 x USB (Unspecified Type) Power PoE Support PoE+ 802.3at Power Connectors 1 x Barrel / Coaxial (12 VDC) Environmental Operating Temperature 14 to 122° F / -10 to 50°C Operating Humidity 80% General Tripod Mounting Thread 1/4"-20 Female Dimensions 6.3 x 7.01 x 8.66" / 16 x 17.8 x 22 cm Weight 4.1 lb / 2 kg Packaging Info Package Weight 7.25 lb Box Dimensions (LxWxH) 12.4 x 12.3 x 9.9"</p>
<p>V12PDDX4Y-IP V-SERIES DESKTOP 12PUSHBUTTON XLR4: IP ENABLED</p>	<p>CLEAR-COM</p>	<p>V12PDDX4Y</p>	<p>2</p>	<p></p>	<p>1</p>	<p>2</p>	<p>Front Panel Controls &amp; Connectors Talk/Listen Switches: 12 Answer Back Switch: Configurable (None, 1 or 2) Volume Controls: 2 (Main and Aux) Headset Connector: 1 (XLR-4M or XLR-5F) Panel Mic Connector: 1 (3-pin) Rear Panel Connectors GPIO: DB-25F Matrix: RJ-45 (single-channel Matrix (IP): RJ-45 (multi-channel) Auxiliary Audio: DB-25M Expansion Panel: RJ-45 DC Power: 4-pin DIN With AES Option: AES (75 Ohms Co-Ax): BNC (dual channel) AES (CAT5): RJ-45 (dual channel Headset Audio Earphone Impedance: From 32 Ohms Output Power: 75mW into 50 Ohms for &lt;1% distortion Loudspeaker Audio Frequency Response: 40Hz-20KHz +/- 3dB Panel Microphone Input Type: Electret Level: 40-70 dBu Impedance: 1700 Ohms +/- 10% Headset Microphone Input Type: Dynamic or Electret Level: -40 - 0 dBu Main Power Supply (External) Voltage: 100/240 VAC +/- 10% Frequency: 50 - 60 Hz Power: 50W maximum Environmental Operating: +32° - +125° F (0° - +50° C) Storage: +32° - +150° F (0° - +70° C) Humidity: Between 20% and 90%, Non Condensing Dimensions 5.9 x 10.25 x 6.75 (HxWxD) (150 x 260 x 172 mm) Weight 6.0 lbs (2.75 kg)</p>
<p>Totals</p>			<p></p>	<p></p>	<p></p>	<p></p>	<p></p>