

SMPTE Purchase

RFI Line Items

Product name	MFR	MFR product #	ECPU	Min qty	PMP	PAP	PF	ETD	Details
LEMO PUW to Dual ST In-Line Fiber Optic Breakout Cable - 6 F	Camplex	HF-PUWST-BO-006		1			1	2	Connector 1 PUW Connector 2 ST Coupling Type LEMO (SMPTE Cable Length 6' / 1.8 m. Assembled with premium SMPTE cable & LEMO and Senko connectors Industry standard cable Terminations by LEMO trained technicians Fiber optic assemblies 100% tested for attenuation and back reflection SMPTE 311M and 304M compliant Stainless steel assemblies Rubber dust caps 19.4 Mb/s to 3 Gb/s transport speed Machine polished fiber contacts Low insertion and return loss
LEMO FUW to Dual ST & 6-Pin RG In-Line Fiber Breakout 6 Foot	Camplex	HF-FUWST8-BO-006		1			1	2	Certified multistage machine-polished cable and features LEMO FUW, Duplex ST, and 6-pin connectors. It meets SMPTE specifications. Industry standard cable assembled with premium SMPTE cable, and LEMO and Senko connectors Terminations done by LEMO trained technicians Electrical assemblies 100% tested for continuity and short circuits Fiber optic assemblies 100% tested for attenuation and back reflection SMPTE 311M and 304M compliant Stainless steel assemblies Rubber dust caps 19.4 Mb/s to 3 Gb/s transport speed Machine-polished fiber contacts Low insertion and return loss. Connector 1 FUW Connector 2 ST 6-Pin AMP Coupling Type LEMO (SMPTE Cable Length 6' / 1.8 m
Totals									