

Ballasts & Light Bulbs

RFI Line Items

ECPU:ESTIMATED COST P/UNIT

PMP:POTENTIAL MINIMUM PURCHASE

PAP:POTENTIAL ANNUAL PURCHASE

PF:PURCHASE FREQUENCY

ETD:ESTIMATED DELIVERY TIME

| Product name | MFR | MFR product # | ECPU | Min qty | PMP | PAP | PF | ETD | Details |
|--|-----------------|----------------------|------|---------|-----|-----|----|-----|--|
| 2 Lamp T8 Ballast | Sylvania | S5208 | | 20 | | | 2 | 3 | 2 Lamp Universal Electronic Sylvania Ballast for 4' T8 Fluorescent Sylvania Light Bulb |
| 2 Lamp T8 Ballast | Sylvania | ICN2M32MC | | 20 | | | 6 | 3 | 2 Lamp - 120/277 volt - T8 - ICN-2M32 -MC - Instant Start - Electronic - Centium Advance Fluorescent Ballast |
| 3 Lamp T8 Ballast | Sylvania | 49945 | | 20 | | | 6 | 3 | (3) Lamp - F32T8 - 120/277 Volt - Instant Start - 0.88 Ballast Factor - QTP3X32T8/UNV/ISN |
| 4 lamp T8 Ballast | Sylvania | QTP4X32T8/UNV/ISN | | 20 | | | 4 | 3 | OSRAM SYLVANIA QTP4x32T8/UNV-ISN-SC (49947) 4 FLUORESCENT Ballasts- Fluorescent-HID |
| 13 Watt CFL Ballast | Advance | ICF2S13H1LD35M | | 20 | | | 2 | 3 | for use with (2) 13Watt CFL (4PIN) 120277Volt compact fluorescent lamps |
| (2) 26 Watt CFL Ballast | Advance | IZT-2S26-M5-BS | | 20 | | | 2 | 3 | FOR 1OR 2 26 WATT CFL PIN LIGHTS |
| 54 WATT T5 Ballast | Universal | B254PUNV-D 2 Lamp T5 | | 10 | | | 6 | 3 | Brand Universal - Family AccuStart 5 - Voltage 120/277 - Ballast Factor 1 - Length 16.88 in. - Width 1.18 in. - Height 1 in. - Start Temp. Min 0 Deg. F - Power Factor 99 - Start Method Programmed Star |
| 26 Watt CFL Ballast | Universal | QTP 2x26/32/42CF/UNV | | 20 | | | 2 | 3 | IntelliVolt? multiple-voltage technology enables operation at any input voltage from 120 to 277 volts, 50/60Hz |
| 42 Watt CFL Ballast | Universal | 23829 | | 20 | | | 2 | 3 | C2642UNVME 000K 1 or 2 Lamp - 120 to 277 Volts - Operates 26/32/42 Watt Triple Tube Lamps, 26 Watt Quad Tube, 24 Watt Linear - Operates 28 and 32 Watt Butterfly Lamps (F282D/F382D) |
| 4 lamp T12 Ballast | Universal | B432I277RH | | 10 | | | 6 | 3 | Universal Triad B432I277RH-A T8 Fluorescent Ballast |
| (1-4) T12/HO4 32 ft Ballast | Philips Advance | ISB043214EI | | 10 | | | 2 | 3 | Ballast, Fluorescent, Electronic, Instant Start, High Output |
| Electronic Sign Ballast - 4-32 ft. Total | Hatch | ESB-0432-14-UV | | 10 | | | 2 | 3 | electronic sign ballast features instant start circuitry, is RoHS compliant, and can be used with up to (4) T12/HO 800mA lamps |

Ballasts & Light Bulbs

| Product name | MFR | MFR product # | ECPU | Min qty | PMP | PAP | PF | ETD | Details |
|--|-----------|---------------------|------|---------|-----|-----|----|-----|--|
| T5 Fluorescent Ballast | Universal | B224PUNV-C | | 20 | | | 4 | 3 | F24T5HO |
| (2) Lamp - F96T12/HO/ES | Universal | B295SRUNVHP000C | | 20 | | | 4 | 3 | 120/277 Volt - Instant Start - 0.88 Ballast Factor |
| T8 Fluorescent Ballast | Sylvania | 49906 | | 20 | | | 5 | 3 | Instant Start Electronic Fluorescent Ballast for (1-2) F32T8 F40T8 F17T8 Lamps Operated at 120V/277V - QTP2X32T8/UNV-ISN-SC-B |
| PLL40/41K 4-PIN Compact Fluorescent 2G11 Base | Philips | 30044 | | 50 | | | 4 | 2 | 40 Watt Compact Fluorescent 4100 Kelvin Color Temperature 4-Pin 2G11 Base 3150 Lumens 82 CRI, 20,000 Average Rated Hours 16.5" Maximum Overall Length. |
| PLL40/830K 4-PIN Compact Fluorescent 2G11 Base | Philips | 30042 | | 50 | | | 4 | 2 | 40 Watt Compact Fluorescent 3000 Kelvin Color Temperature 4-Pin 2G11 Base 3150 Lumens 82 CRI, 20,000 Average Rated Hours 16.5" Maximum Overall Length. |
| CF26DD/E/841/ECO | Sylvania | 20669 | | 100 | | | 4 | 2 | 26-Watt Double Tube Compact Fluorescent Light Bulb, 4100K, 1710 Lumens, 82 CRI, T4 Shape, 4-Pin G24q-3 Base, 12-pack |
| 7MR16/F25 3000 DIM AF2 10/1 | Philips | 929001152904 | | 48 | | | 4 | 2 | |
| FO32/841/ECO | Sylvania | FO32/841/ECO | | 420 | | | 4 | 2 | 32 Watt 48" T8 Linear Fluorescent 4100K 85 CRI Medium Bipin (G13) Base Tube |
| F96T12/CW/HO-O/ALTO | Philips | 38176-4 | | 15 | | | 5 | 2 | 110 Watt - T12 - High Output - 4100K - Case of 15 |
| F72T12/CW/HO/ALTO | Philips | 36651-8 | | 15 | | | 4 | 2 | 85 Watt - T12 - High Output - 4100K - Case of 15 |
| F84T12/CW/HO | Sylvania | 25384 | | 15 | | | 5 | 2 | Straight T12 Fluorescent Tube Light Bulb 4100K |
| F54T5/841/HO/ECO LAMP | GE | F54W/T5/841/ECO/SRC | | 40 | | | 3 | 2 | 54 Watt 46" T5 Linear Fluorescent 4100K 85 CRI Miniature Bipin (G5) Base Shatter Resistant Coated High Output Tube |
| 8.5A19/27K/CL/ND | Philips | 462309 | | 50 | | | 4 | 2 | 60 Watt Equivalent Soft White A19 LED Clear Light Bulb, 8 Pack |
| 13PAR30/LN/LED/40'/2700K/120V/D | SATCO | S9430 | | 24 | | | 4 | 2 | 13 watt PAR30 Long Neck LED; 2700K; 40' beam spread; Medium base; 120 volts |

Ballasts & Light Bulbs

| Product name | MFR | MFR product # | ECPU | Min qty | PMP | PAP | PF | ETD | Details |
|------------------------------------|----------|---------------|------|---------|-----|-----|----|-----|---|
| 13PAR30/SN/LED/40'/2700K/120V/FL | SATCO | S9415 | | 24 | | | 4 | 2 | LED PAR30 Bulb Short Neck - 13W - 75W Equivalent - 950 Lumens - 2700K |
| 3.5W CTC/LED/27K/CL/120V | SATCO | S9922 | | 10 | | | 4 | 2 | 3.5 watt C11 LED; Clear; Candelabra base; 2700K; 350 lumens; 120 volts |
| 6G25/LED/2700K/450L/120/DIMMABLE | SATCO | S9200 | | 24 | | | 4 | 2 | 6 watt; G25 Globe LED; 2700K; Medium base; 120 volts |
| 7PAR20/LED/40'/3000K/120V/DIMMABLE | SATCO | S9082 | | 24 | | | 4 | 2 | 7 watt; LED PAR20 LED; 3000K; 40' beam spread; Medium base; 120 volts |
| 4.5T10/LED/E26/27K/120V | SATCO | S9580 | | 30 | | | 4 | 2 | 4.5 watt T10 LED; Clear; Medium base; 2700K; 430 lumens; 120 volts |
| ADVANCE CENTIUM ICN-2M32-MC | Philips | ICN-2M32-MC | | 40 | | | 2 | 2 | Fluorescent Ballast: For Fluorescent, Electronic, Instant, 0° F Min Starting Temp, 59 W Input Watt |
| QUICKTRONIC Electronic Ballasts | Sylvania | CF26/32/42 | | 20 | | | 4 | 2 | CF26/32/42 120/277V BALLAST UNIVERSAL |
| FO32/830/ECO | Sylvania | 21777 | | 300 | | | 3 | 2 | 48" long, 3000K color temperature, 82 CRI, 32 watts, Energy efficient, operates on an electronic ballast. |
| Totals | | | | | | | | | |