

Wall Mounted Air Conditioning System

RFI Line Items

ECPU:ESTIMATED COST P/UNIT

PMP:POTENTIAL MINIMUM PURCHASE

PAP:POTENTIAL ANNUAL PURCHASE

PF:PURCHASE FREQUENCY

ETD:ESTIMATED DELIVERY TIME

| Product name | MFR | MFR product # | ECPU | Min qty | PMP | PAP | PF | ETD | Details |
|---|-----|---------------|------|---------|-----|-----|----|-----|---|
| MSZ-GS36NA Indoor Wall Mounted Air Conditioning System | | | | 5 | | | 1 | 5 | INDOOR UNIT FEATURES • Dual Barrier Coating • Slim wall-mounted indoor units provide zone comfort control • The outdoor unit powers the indoor unit, and should a power outage occur, the system is automatically restarted when power returns • Multiple fan speed options: Low, Medium, High, Super High* • Multiple control options available: <input type="checkbox"/> Hand-held Remote Controller (provided with unit) <input type="checkbox"/> kumo cloud® smart device app for remote access <input type="checkbox"/> Third-party interface options <input type="checkbox"/> Wired or wireless controllers • Hot-Start Technology: no cold air rush at equipment startup or when restarting after defrost cycle • Powerful Operation: quickly cools or heats the room by automatically adjusting fan speed and set temperature for 15 minutes • Smart Set: recalls a preferred preset temperature setting at the touch of a button • Wide Vane mode provides 150° of airflow *Auto and Powerful modes available in addition to the four fan speeds |
| MUZ-GS36NA Outdoor Wall Mounted Air Conditioning System | | | | 5 | | | 1 | 5 | OUTDOOR UNIT FEATURES • INVERTER-driven compressor and LEV provide high efficiency and comfort while using only the energy needed to maintain maximum performance • Blue Fin HEX coating |
| Totals | | | | | | | | | |