		Sheet Number: 11.0			
e miami-dade		Product Specifications			
Miami Dade Water & Sewer Depa Address: 3071 SW 38th Ave, Mia Phone: (305) 665-7477 Email: WASD-STANDARDS@mi	mi, FL 33146	SUBMERSIB	LE PUMPS U	Р ТО 60 НР	
	Minimum Standa • ASTM • AWWA • WASD Specificat 33 32 13 (02540)	ions: Sections 33 32 11.	11 (11205),		
	 Permanent Type Must be tested fo Dotted lines withi Department. NPSHr curve mu Motor speeds up Maximum weight The Department 	 Dotted lines within pump performance curves require to be approved by the Department. NPSHr curve must be provided. Motor speeds up to 3,600 rpm. 			
	 Applications Wastewater Installation (Wet 1) 	Well or Dry Well)			
PRE-APPROVED MANUFACTURER 1) FLYGT 2) SULZER			Issue Date: 10/26/2023		
3) GRUNDFOS 5) SHINMAYWA	4) VAUGHAN		Revised Dat	e:	
APPROVED PRODUCTS			<u>1</u>		
MANUFACTURER	DESCRIPTION			SUBMITTED	
	N 3000, F 3000			_	
FLYGT	N 3000, F 3000				
FLYGT SULZER	N 3000, F 3000 ABS XFP - Contrablock Plus Imp	eller			
		eller			
SULZER	ABS XFP - Contrablock Plus Imp	eller			
SULZER GRUNDFOS	ABS XFP - Contrablock Plus Imp SLV, SEV - Vortex Impeller	eller			
SULZER GRUNDFOS GRUNDFOS	ABS XFP - Contrablock Plus Imp SLV, SEV - Vortex Impeller SL, S - S Tube Channel Impeller				
SULZER GRUNDFOS GRUNDFOS GRUNDFOS	ABS XFP - Contrablock Plus ImpSLV, SEV - Vortex ImpellerSL, S - S Tube Channel ImpellerSE - S Tube Open Impeller	r			

1

SHINMAYWA	CNX Series Submersibles Double Vane Enclosed	
SHINMAYWA	CNXH, Series Submersibles Single Vane Enclosed	
COMMENTS:		
Approved by: MDW	ASD Departmental Standards, Specifications and Products Co	mmittee, PSCS, PSD.
Revision History		
Revision History		